

DERWENT-ACC-NO: 1991-041095  
DERWENT-WEEK: 199106  
COPYRIGHT 1999 DERWENT INFORMATION LTD

TITLE: Highly damping rubber compsn. - contg. e.g.  
styrene-butadiene rubber  
and carbon black

PATENT-ASSIGNEE: TOYO RUBBER IND CO LTD[TOYF]

PRIORITY-DATA: 1989JP-0130694 (May 23, 1989)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE
PAGES	MAIN-IPC	
JP 02308835 A	December 21, 1990	N/A
N/A		000

APPLICATION-DATA:

PUB-NO	APPL-DESCRIPTOR	APPL-NO
APPL-DATE		
JP02308835A	N/A	1989JP-0130694
May 23, 1989		

INT-CL\_(IPC): C08L021/00; C08L023/26 ; C08L071/02

ABSTRACTED-PUB-NO: JP02308835A

BASIC-ABSTRACT: Rubber compsn. comprises a rubber component and carbon black, where (a) content of styrene-butadiene-rubber which contains bonded styrene is 10-52% and mol.wt. is  $5 \times 10^3$  -  $2 \times 10^5$ , (b) content of carbon black is 15-50 pts.wt. (whose iodine adsorbing specific surface area (IA) is 20-100 mg/g and DBP value is 50-120 cm<sup>3</sup>) per 100 of the rubber compsn., and (c)

tan-delta of the compsn. is at least 0.25.

The rubber component is pref. a low mol.wt. rubber . Crosslinked segment and uncrosslinked segment can be supplemented by the admixed presence of rubber components which gives high damping and vibration proofness.

ADVANTAGE - Prod. requires no dampers, giving reduced work period and cost.

Prod. gives high loss characteristics without impairing the low

creep  
characteristics, low temp. dependency, and resistance to damage.

CHOSEN-DRAWING: Dwg.0/0

T

---